

## TS-7 - Soft Start Push Button Timer - 6kW



Application	Controlling halogen heaters (including patio heaters)
Mounting	Surface
Finish	Light grey
Time delay	5 minutes to 90 minutes
Switching capacity	6kW 230V (250W minimum)
Voltage supply	230V
Contacts	Single pole, single throw
Dimensions	124mm x 124mm x 78mm
Ingress protection	IP65
Special features	Constant light indicates 'heater on' Flashing light indicates last minute of operation Can be used with our PROTIM-7 timer or a volt free thermostat such as our PROSTAT2 Soft start switching prolongs halogen lamp life Supplied with 2 x M20 cable glands

## TS-7B - Soft Start Push Button Timer - 6kW



Application	Controlling halogen heaters (including patio heaters)
Mounting	Surface
Finish	Black
Time delay	5 minutes to 90 minutes
Switching capacity	6kW 230V (250W minimum)
Voltage supply	230V
Contacts	Single pole, single throw
Dimensions	124mm x 124mm x 78mm
Ingress protection	IP65
Special features	Constant light indicates 'heater on' Flashing light indicates last minute of operation Can be used with our PROTIM-7 timer or a volt free thermostat such as our PROSTAT2 Soft start switching prolongs halogen lamp life Supplied with 2 x M20 cable glands

## TS-8 - Push Button Timer - 7.2kW



Application	Controlling electric heaters including ceramic heaters, fan heaters Ideally suited for use with a contactor Not suitable for direct switching of halogen heater (i.e. only via contactor)
Mounting	Surface
Time Delay	5 minutes to 90 minutes
Switching Capacity	7.2kW 230V (no minimum)
Voltage Supply	230V
Contacts	Single pole, single throw
Dimensions	124mm x 124mm x 78mm
Ingress protection	IP65
Special features	Constant light indicates 'heater on' Flashing light indicates last minute of operation Can be used with our PROTIM-7 timer or a volt-free thermostat such as our PROSTAT2 Supplied with 2 x M20 cable glands

## PROTIM-7 - Programmable Timer



Application	Ideal for use with a variety of commercial and industrial heating schemes
Programming	7day, 5 + 2 days or 24hour
Mounting	Surface
Maximum events per day	4
Switching Capacity	13A 230V (when switching halogen heaters this timer can be used in conjunction with our SSR soft start relay - see page 142)
Voltage Supply	230V
Dimensions	90 x 115 x 57mm
Ingress Protection	IP30
Special Features	Advance to next programme Boost (select 1 hour or 2 hours) Override - permanently on or permanently off Automatic summer update Battery back up Tough aluminium case